







Sustainability Initiatives SP MAE Workshops



Speaker 1: Mr Saw Tun



- Senior Lecturer, School of Mechanical & Aeronautical Engineering, Singapore Polytechnic
- Course Manager for CET Specialist Diploma for Air-Conditioning & Energy Sustainability
- Course Coordinator for Short Courses related to Building Information Modelling (BIM)
 applications in BE industry
- Lead for MAE's Focus Group: Energy & Sustainability



MAE's Motivation

Why Sustainability?



- Sustainability targets
- Influence and enabler of green efforts



- 60-30 Vision, 5% energy reduction challenge
- Reduce Waste Disposal Index by 30% by FY2030
- Reduce Water Efficiency Index by 10% by FY2030



- Industry Trends
- Prepare our learners
- Journey with companies



Singapore's Sustainability Vision

GreenGov.SG - Targets for public sector

Focus Area	Target
Greenhouse Gas Emissions	Net zero emissions around 2045, after peaking emissions around 2025
Energy	Reduce energy use by 10% from the baseline by 2030
Water	Reduce water use by 10% from the baseline by 2030
Waste	Reduce waste disposed of by 30% from the baseline by 2030



Singapore's Sustainability Vision

GreenGov.SG - Targets for public sector

Focus Area

Target



Greenhouse Gas Emissions

Net zero emissions around 2045, after peaking emissions around 2025

SP's Sustainability Vision

60-30 Vision at a Glance





PCEO's challenge to further reduce 5% of EUI by 2025.

Source: https://www.greenplan.gov.sg/key-focus-areas/green-government/



What are the industry trends?

Carbon tax: Singapore's carbon tax steadily increases to drive decarbonization and incentivize low-carbon technologies.

Sustainability disclosures (Scope 1 and 2): From FY2025, SGX-listed companies must report direct and indirect emissions, enhancing transparency and climate accountability.

Scope 3 disclosures in FY2026: From FY2026, listed firms will need to disclose Scope 3, covering value chain impacts and pushing broader climate responsibility.

Large Non-Listed Companies (FY2027): From FY2027, large private firms must adopt similar sustainability disclosures, aligning them with public company standards.

Regulations beyond Singapore: Global sustainability regulations are tightening, pushing companies to adopt consistent climate reporting across jurisdictions.



1. Build Capabilities

- Assign dedicated team
- Build knowledge
- Engage industry and solution providers

2. Planning & Baselining

- Conduct energy audit & baselining
- Implement energy monitoring system

3. Implement & Improve

- Prioritise and implement sustainability measures
- Replace the old AC equipment with more energy efficient equipment



1. Build Capabilities

- Assign dedicated team
- Build knowledge
- Engage industry and solution providers

Build Knowledge

- Green Compass (Sep 2022)
- Masterclass in Sustainability by SMF (Sep 2023)
- Leading the Manufacturing Sustainability by SMF (Feb 2024)
- Carbon Management & Strategies in Driving Net Zero (Feb 2024)
- Sustainable Manufacturing Awareness (SIRI & COSIRI) (Mar 2024)
- ISO 50001: Energy Management System Implementation (Sep 2024)










Energy Audit & Baselining

2. Planning & Baselining

Energy Audit @W1411 & W1412B

Conduct energy audit & baselining



- To establish an energy baseline by assessing energy consumption breakdown and identifying energy-saving opportunities.
- Level 2 energy audit was performed.


Energy Audit & Baselining: Energy Consumption Breakdown

2. Planning & Baselining

Energy Audit @W1411 & W1412B

Conduct energy audit & baselining

System	Est Annual Energy Consumption (kWh/Year)
AC VRV System	76,872.00
Lighting System	12,336.48
Compressed Air System	4,715.10
CNC Machines	3,900.00
Others	6,570.00
Total Consumption:	104,393.58
GFA (m ²)	659.00
Energy Utilization Index, EUI (kWh/m²)	158.41



Energy Audit & Baselining: Energy Consumption of AC system

2. Planning & Baselining

Conduct energy audit & baselining

Energy Audit @W1411 & W1412B

Energy (kWh) = Energy Efficiency (kW/RT) x Cooling Load (RT) x Time (h)

Location	Area (m2)	Weighted Cooling Load, RT	Cooling Load Intensity, m2/RT					
W1411	507.58	23.23	21.85					
W1412B	151.42	13.25	11.43					
Total	659	36.47	18.07					

System	Weighted Cooling Load (RT)	Weighted input power (kW)					
VRV CU	36.47	28.28					
VRV FCU		6.88					
Total	36.47	35.16					
TSE	0.964	kW/RT					



Energy Audit & Baselining: Energy Saving Opportunities

2. Planning & Baselining

Conduct energy audit & baselining

Energy Audit @W1411 & W1412B

System	Proposals	Est. Reduction from Total Consumption (%)
AC VRV System	 W1411: Operate half the VRV fan coil units to achieve a cooling load intensity between 30 and 40 m²/RT. W1412B: Operate half the VRV fan coil units during the peak and operate only 1 fan coil unit during off-peak. 	22.49%
Lighting System	 Use more <u>energy efficient lightings</u>, reducing lighting budget from 5 W/m² to 3.5 W/m². 	4.92%
Compressed Air System	 Reduce operating pressure from 8 bars to 6 bars. Install variable speed drive (VSD) for the compressor to operate at lower speed and pressure. 	1.15%

Est. total reduction (%) = 29%

Est. total energy reduction = 29,820 kWh

Potential EUI reduction to 113.16 kWh/m²/year from 158.41 kWh/m²/year




Energy Monitoring System: Implementation


2. Planning & Baselining

- Conduct energy audit & baselining
- Implement energy monitoring system

• Purpose: Gather data to <u>review energy efficiency implementation</u> and continuously monitor systems for <u>sustained performance</u>.










2. Planning & Baselining

- Conduct energy audit & baselining
- Implement energy monitoring system

Energy Monitoring System: Dashboard

Installed <u>15 new power meters</u>, <u>1 water meter</u>, <u>and set up a dashboard</u> incorporating our existing power meters for near real-time monitoring.





3. Implement & Improve

 Prioritise and implement sustainability measures

Prioritise and Implement Sustainability Measures

Energy Saving Measures

System	Proposals	Est. Reduction from Total Consumption (%)
AC VRV System	 W1411: Operate half the VRV fan coil units to achieve a cooling load intensity between 30 and 40 m²/RT. W1412B: Operate half the VRV fan coil units during the peak and operate only 1 fan coil unit during off-peak. 	22.49%
Lighting System	Use more <u>energy efficient lightings</u> , reducing lighting budget from 5 W/m² to 3.5 W/m².	4.92%
Compressed Air System	 Reduce operating pressure from 8 bars to 6 bars. Install variable speed drive (VSD) for the compressor to operate at lower speed and pressure. 	1.15%



Energy Saving Measures

3. Implement & Improve

 Prioritise and implement sustainability measures

System	Proposals	Actual Reduction from System Consumption (%)
	• W1411: Operate half the VRV fan coil units to achieve a cooling load intensity between 30 and 40 m ² /RT.	Oct – Dec 2024: 27,154.2kWh
AC VRV System	<u></u>	Jan – Mar 2025:
	 W1412B: Operate <u>half the VRV fan coil units</u> during the peak and operate only 1 fan coil unit 	19,466.5 kWh
	during off-peak.	28% reduction
Lighting System	Use more <u>energy efficient lightings</u> , reducing lighting budget from 5 W/m² to 3.5 W/m².	4.92%
	• Reduce operating pressure from 8 bars to 6 bars.	Oct – Dec 2024: 3961.8 kWh
Compressed Air System	 Install <u>variable speed drive (VSD)</u> for the compressor to operate at lower speed and pressure. 	Jan – Mar 2025: 3010.2 kWh
		24% reduction

Prioritise and Implement Sustainability Measures

Energy reduction over 3 months = 8,639.3 kWh

Cost reduction over 3 months (based on \$0.3 per kWh) = \$2,591.79




3. Implement & Improve

- Prioritise and implement sustainability measures
- Replace the old AC equipment with more energy efficient equipment

Replace the old AC equipment with more energy efficient equipment

Upgrading energy efficient air handling system at W1311-RAC Lab

- Air Handling Unit (AHU) system used in our Refrigeration & Air-Conditioning RAC lab was ageing and there is no energy monitoring and energy efficient features.
- Upgraded to a new air handling system equipped with energy-saving technologies.







3. Implement & Improve

- Prioritise and implement sustainability measures
- Replace the old AC equipment with more energy efficient equipment

Replace the old AC equipment with more energy efficient equipment

Upgrading energy efficient air handling system at W1311-RAC Lab

Energy (kWh) = Energy Efficiency (kW/RT) x Cooling Load (RT) x Time (h)

Case 1: Before the	AHU U	pgra	<u>de</u>				Room	Cond	<u>lition</u>				
Chiller Power =	12	kW				Temp (deg C):			20				
AHU Power =	3	kW					RH (%):		85				
Total Power =	15	kW											
Cooling Load =	5.57	X	4.2	(14	-	11) =	70.182	kW	=	20.0	RT
COP =	70.2	/	1 5	=	4.6788								
kW/RT =	0.75												
Energy per day =	20.0	Х	0.75	Х	8	=	120	kWh					

Case 2: After the A	HU Up	grade	2				Room	Cond	dition_				
Chiller Power =	12	kW				Tei	mp (de	g C):	24				
AHU Power =	0.53	kW					RH	(%):	55				
Total Power =	12.5	kW											
Cooling Load =	0.37	X	4.2	(17.50	-	9.60) =	12.277	kW	=	3.5	RT
COP =	12.3	/	12.5	=	0.98								
kW/RT =	3.59												
Energy per day =	3.5	Х	3.59	Х	8	=	100	kWr	1				

Energy reduction per year = $\frac{4,800 \text{ kWh}}{4,800 \text{ kWh}}$ (more than 16% saving from air side system)

Cost reduction per day (based on 0.3 per kWh) = 1.440



3. Implement & Improve

- Prioritise and implement sustainability measures
- Replace the old AC equipment with more energy efficient equipment

Replace the old AC equipment with more energy efficient equipment

Upgrading energy efficient air handling system at W1311-RAC Lab

Case 2: After the A	HU Up			Room	Cond	dition							
Chiller Power =	12	kW				Ter	Temp (deg C):		24				
AHU Power =	0.53	kW					RH	(%):	55				
Total Power =	12.5	kW											
Cooling Load =	0.37	X	4.2	(17.50	-	9.60) =	12.277	kW	=	3.5	RT
COP =	12.3	/	12.5	=	0.98								
kW/RT =	3.59												
Energy per day =	3.5	Х	3.59	Х	8	=	100	kWr					

- From the air system upgrade, able to reduce more than 16% of the energy consumption
- Still have great potential to further reduce the energy by upgrading the water side
- Will include upgrading the existing chilled water and condenser water pumps and cooling tower with variable speed drive (VSD)
- Target to stretch the energy saving more than 40%



MAE Sustainability Courses

Specialist Diploma in Air-Conditioning & Energy Sustainability (1-Year Programme)

- Air-Conditioning & Energy Sustainability
 - ➤ Air-Conditioning System
 - Green Mark & Energy Sustainability
- Energy Modelling & Management
 - Integrated Building Management System
 - Information & Energy Modelling of Facility

Specialist Diploma in Sustainable Digital Manufacturing (1-Year Programme)

- Manufacturing Digitisation
 - > Al-Driven Data Analytics for Sustainable Manufacturing
 - Essentials of Advanced Manufacturing
- Monitoring and Reporting for Sustainability
 - Sustainability Reporting and Strategies
 - Energy Monitoring and Auditing



MAE Sustainability Courses

Short Courses

- [SSG approved] Driving Sustainability in Manufacturing Through ISO 50001 Energy Management Approach (co-developed with TUV SUD)
- **[SSG approved]** Performing Fundamental Greenhouse Gas Accounting Based on ISO 14064 A Manufacturing Perspective (co-developed with TUV SUD)
- [SSG approved] Sustainability Roadmap Implementation for Manufacturing Industry (co-developed with SMF)

MAE Sustainability Courses





Programme Benefits

Foundations of Sustainable Manufacturing

Gain insights into the core principles, benefits, and impact of sustainable manufacturing on SMEs.

Structured Implementation

Understand the three-stage sustainability journey and apply Phase 1 (Planning) by setting objectives, identifying KPIs, and engaging stakeholders.

Practical Application

Identify a Proof-of-Concept (POC) focus area for mentoring and validation with HP Singapore at Phase 2.

Applicable Industries

SMEs with manufacturing facilities in aerospace, electronics, food and beverage (F&B), fast-moving consumer goods (FMCG), general manufacturing, pharmaceutical, and precision engineering

Phase 1

Phase 2

Phase 3

2-Day Business Needs Analysis in Sustainable Manufacturing Workshop 4-Hour Proof of Concept
Mentoring Programme with HP

Evaluation and Implementation



Speaker 2: Mr Ahmad Sulaiman B. Sumani, CEng



- Adjunct Lecturer, School of Mechanical & Aeronautical Engineering, Singapore Polytechnic
- Practicing BCA Energy Auditor and Energy Efficiency Opportunities Assessor
- 40 Years Experience In The Field of Air-conditioning
- Holders of 2 patent On Data Analytics

Misconception On Environmental Sustainability



- 1. Which Come First? Environmental Sustainability Or Design In-built Environmental Objectives
 - a. Environmental Sustainability Energy Savings, Cost Savings, Carbon Reduction
 - b. Design In-built Environmental Objectives Space Temperature, Humidity and CO2 concentration

- 2. Can Be Done In Isolation?
 - a. Yes or No?

Energy Savings & Energy Cost Savings



S\$ = kWh x Tariff

S\$ = **kW** x **Hours of Operations** x Tariff

S\$ = Load(RT) x Efficiency(kW/RT) x Hours of Operations x Tariff

S\$ = Area(m2) x Intensity(m2/RT) x Efficiency(kW/RT) x Hours of Operations x Tariff

Opportunity 1
Can We Reduce
the AC Area?

Opportunity 2
Can We Used Less
Cooling Load Per Area?

Opportunity 3
Can We Operate The AC More Efficiently?

Opportunity 4
Can We Operate Based
On Occupancy Mode?

Opportunity 5
Can We Negotiate
For Better Tariff?

Concept of Energy Efficiency and Savings



1. Conceptualised and Delivered

- a. Computation Must Accurate and Conservative
- b. Finance Director and the Housewives Must Saw It In Their Utilities.

2. Get Your Priorities/Objectives In The Right Order

a. Primary Objectives – Space Temperature, Relative Humidity and CO2 Concentration

- i. Keep It Simple Make Sure The Operators Could Operate It With Ease
- ii. Follow Through Simplify Your Performance Metrics For The Operator


b. Secondary Objectives – Energy Efficiency and Savings

- Know Your Daily Load, RT and Efficiency Target, kW/RT
- ii. Track Your Operating Performance Hourly initial Stage On-The-Job-Training
- iii. Follow Through Hourly Daily Weekly Monthly Efficiency Target
- iv. Make your Achievement Visible
- v. Final Litmus Test The Savings Must Be Visible In The Monthly Utilities Bill

Setting Up and Delivering Your Primary Objective




- 1. Understand Your HVAC Psychrometric Plan
 - a. Temperature Controls
 - b. Relative Humidity Controls
 - c. CO2 concentration Controls



- a. Designed Space Temperature
- b. Designed Relative Humidity Dew Point
- c. Designed Air Change CO2 Concentration

- 2. Set Up Your Installation As Per Item 1
 - a. Temperature Controls
 - b. Relative Humidity Controls
 - c. CO2 concentration Controls
 - d. Airside Efficiency



- a. Space Temperature RA Thermostat
- b. Relative Humidity Dew Point Sensor
- c. CO2 Concentration CO2 Sensor
- d. Airside Efficiency Digital Power Meter

- 3. Synchronise Your Control And Its Algorithm
 - a. Temperature Controls
 - b. Relative Humidity Controls
 - c. CO2 concentration Controls
 - d. Airside Efficiency



- a. RA Thermostat Fan Speed
- b. Dew Point Sensor Modulating CHW Valve
- c. CO2 Sensor FA Damper
- d. Airside Efficiency Digital Power Meter

- 4. Monitor, Track and Deliver The Performance
 - a. Temperature Controls
 - b. Relative Humidity Controls
 - c. CO2 concentration Controls
 - d. Airside Efficiency
 - e. Load Reduction

- a. RA Thermostat Fan Speed Space Temperature
- b. Dew Point Sensor Modulating CHW Valve Relative Humidity
- c. CO2 Sensor FA Damper CO2 Concentration
- d. Airside Efficiency Digital Power Meter kW/RT
- e. Load Reduction Cooling Load Intensity < m2/RT

Plan and Set Up

SP Singapore Polytechnic

Proposed

Objectives:

1. Temperature: 24 – 26°C

2. Relative Humidity: 65 ± 5%

3. CO2 Concentration: < 1,100 ppm

Existing

<u>Objectives:</u>


1. Temperature: 24 – 26°C


2. Relative Humidity: 65 ± 5%

3. CO2 Concentration: < 1,100 ppm

		A1	95 100	788 710			
SINGAPO	DRE POLYTECHNIC	200	******	********			
PSYCH	HROMETRIC CHART	03	90 0	ERCENTAGE SATURATION TO THE PROPERTY OF THE PR	0 40		
		03	ATVITUS	MINIMA		025	
May 21 9		. 3	АМИ	M M M		023	
h.	40	7				022	2.2
p.	4.3	,	AIMMIN			021 8	
D. SENSIBLE HEAT	5 0.1		AKUMU.	Man Mark		020 2	F R
b.s FACTOR	5 . 1	1. 4		HANHA		010 0	-8
5.5	and and general	LUTE " THE	/ KUP	WITH A		017 &	E =
F.:	8 0.3	0.07	1 1 2			016 010	-8
Fr.	K . J	AND THE				014	N.
Manda Maria	. 1					012 2	. "
deal .	a Till	AKTH VY	ATTAC TO A			012 8	
40	7					010	-8
.)	85	K K X				009	L.
. 7					O. 15	000	
2 7			USK HAN	HT LTH		007	A. B.
33	: ALIMAN HUK		Mark Lines	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		005	8
. 7 .	and the state of t					004	
y 2-100				No.		003	2
						901	12
			P. W. H. J.	N M N	The His	000	
-5 0	5 10 15	20 DDV Ball D	25 30 HOTOATHOE *C	35 40	45		Low
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	adaaaada		43	45	50
444	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	15	20 25	30			


	Т		MODEL	LOCATION			AIR FLOW	TOTAL	TOTAL	TAL OUTSIDE AIR	ENTERING AIR TEMP.		LEAVING	NID TEMP	WATER FLOW	EXTERNAL	POWER		
N	10.	UNIT. NO.		FLOOR	ROOM DESIGNATION	Qty	(L/S)	CAPACITY	SENSIBLE	ENSIBLE FLOW (L/S)	ENTERING AIR TEMP.		LEAVING AIR TEMP.		RATE (I/s) STATIC PRES.		POWER		
				FLOOR	ROOM DESIGNATION		(1/3)	(KW)	HEAT (KW)	FLOW (L/3)	DB (OC)	WB (OC)	DB (OC)	WB (OC)	NATE (I/S)	(Pa)	Volt	ph	kW
	1	AHU-C-FC-01	DM2TB-1519B	CONCOURSE		1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11
	2	AHU-C-FC-02	DM2TB-1519B	CONCOURSE	FOOD COURT	1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11
	3	AHU-C-FC-03	DM2TB-1519B	CONCOURSE	POOD COURT	1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11
	4	AHU-C-FC-04	DM2TB-1519B	CONCOURSE		1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11






Controls Logic


- 1. Fan Speed Constant
- 2. RAT regulate the CHW valve opening
- 3. Room Temperature achieved, the CHW valve closed.
- 4. CO2 sensor/damper not included.
- 5. Result ????




Controls Logic

- 1. Fan Speed Variable
- 2. RAT regulate the fan speed
- DPT regulate the CHW valve opening to maintain a preset DP Temperature
- 4. CO2 sensor regulate FA damper
- 5. Result ????










Set Up, Performance and Efficiency






	UNIT. NO.	MODEL	LOCATION			AIR FLOW	TOTAL	TOTAL	OUTSIDE AIR	ENTERING AIR TEMP.		LEAVING AIR TEMP.		WATER FLOW	EXTERNAL	POWER			
NO.			FLOOR	ROOM DESIGNATION	Qty	(L/S)	CAPACITY (KW)	SENSIBLE HEAT (KW)	FLOW (L/S)	ENTERING AIR TEMP.		LEAVING AIR TEIVIF.		RATE (I/s)	STATIC PRES.	FOWER			
										DB (OC)	WB (OC)	DB (OC)	WB (OC)	MATE (4 sq	(Pa)	Volt	ph	kW	E.
1	AHU-C-FC-01	DM2TB-1519B	CONCOURSE	FOOD COURT 1	1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11	
2	AHU-C-FC-02	DM2TB-1519B	CONCOURSE		1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11	
3	AHU-C-FC-03	DM2TB-1519B	CONCOURSE		1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11	2
4	AHU-C-FC-04	DM2TB-1519B	CONCOURSE		1	6,395	170	101	3,386	25.00	19.50	11.41	11.35	5.21	500	400	3	11	






Controls Logic

- 1. Fan Speed Constant
- 2. RAT regulate the CHW valve opening
- Room Temperature achieved, the CHW valve closed.
- 4. CO2 sensor/damper not included.
- 5. Result ????







Loading 60%


Controls Logic

- 1. Fan Speed Variable
- 2. RAT regulate the fan speed
- 3. DPT regulate the CHW valve opening to maintain a preset DP Temperature
- 4. CO2 sensor regulate FA damper
- 5. Result ????





Cap: 29.0RT



ASE: 0.083 kW/RT

Loading 100%	Cap: 48.3RT	ikW: 11kW	ASE: 0.228 kW/RT
Loading 90%	Cap: 43.5RT	ikW: 11kW	ASE: 0.253 kW/RT
Loading 80%	Cap: 38.6RT	ikW: 11kW	ASE: 0.285 kW/RT
Loading 60%	Cap: 29.0RT	ikW: 11kW	ASE: 0.379 kW/RT
Loading 40%	Cap: 19.3RT	ikW: 11kW	ASE: 0.570 kW/RT

Loading 100% Cap: 48.3RT ikW: 11kW ASE: 0.228 kW/RT
Loading 90% Cap: 43.5RT ikW: 8.0kW ASE: 0.184 kW/RT
Loading 80% Cap: 38.6RT ikW: 5.6kW ASE: 0.145 kW/RT

Loading 40% Cap: 19.3RT ikW: 0.7kW ASE: 0.036 kW/RT

ikW: 2.4kW



Setting Up and Delivering Your Secondary Objective Energy Savings & Energy Cost Savings

- i. Know Your Daily Load, RT and Efficiency Target, kW/RT (RT & kW/RT)
- ii. Track Your Operating Performance Hourly initial Stage On-The-Job-Training
- iii. Follow Through Hourly Daily Weekly Monthly Efficiency Target (RT & kW/RT)
- iv. Make your Achievement Visible (RT & kW/RT)
- v. Final Litmus Test The Savings Must Be Visible In The Monthly Utilities Bill (kWh & \$\$\$)

Conclusion



- 1. Design, Built and Operation In Totality As An Eco-System
- 2. Design For The "Real" Operator To Operate
- 3. Make It Simple For Operations, Performance and Efficiency
- 4. Know Your Real-Time, Hourly, Daily, Weekly, Monthly and Annual Operating Efficiency
- 5. Continuous Training On Operations Performance and Efficiency
- 6. Include Your Operators In Your Monthly Operations Meeting.
- 7. Practice Create Habits, Good Habits Create Performance



Discussion